



ARLON

DPF V9500 **VITAL.**

Transform textured surfaces with DPF V9500, engineered for exceptional conformability for a paint-like finish. It's high-tack adhesive securely adheres to rough surfaces without lifting, shrinking, or popping over time. Designed for effortless installation, DPF V9500 is easily repositionable and has a wide temperature range for hot and cold installations. Keep your graphics looking new with an extended durability of up to 10 years. Plus, its PVC-free, Polyurethane formula makes it the ideal sustainable solution. Elevate any wall with DPF V9500 — built for performance, made for impact.

Unique Features:

- ▶ Unmatched conformability to highly textured surfaces
- ▶ High-tack adhesive to prevent popping or lifting
- ▶ 10-year extended life durability
- ▶ Wide installation temperature range
- ▶ Easy repositionability with an air-ex liner

Applications:

- ▶ Building Wraps
- ▶ Wall Graphics (Interior, Exterior)

Performance & Physical Data

Finish:	Gloss
Durability (Unprinted):	10 Years
Roll Widths:	54" (1,37 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	Permanent, Repositionable (Tinted)
Release Liner:	Lay-Flat Polycoated with Low Profile Air-egress
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlaminates:	Series V3370



USA

- a** 200 Boysenberry Lane, Placentia, CA 92870
- p** 800 232 7161 / +1 714 985 6300
- f** +1 714 985 6305

EUROPE

- a** Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p** +31 70 354 4311
- f** +31 70 355 7721

CHINA

- a** No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p** +86 0536 6226568