

Description

This double-sided tape consists of a textile carrier which is layered on both sides with modified dispersion acrylate adhesive. The adhesive is largely resistant to plasticisers. The adhesive on the covered side of the tape has excellent permanent adhesive qualities. The adhesive on the open side allows easy removal without residues from many surfaces. The adhesive liner is coated with a double sided siliconized paper.

Carrier

Rayon

Liner

55# paper, white, silicone-coated on both sides

Adhesive

Modified dispersion acrylate

Area of Use

This double-sided tape is especially suitable for the installation of carpets at exhibitions (with high cohesion and easy removal). It is also suited for PVC floors and carpets with PVC backsides.

Technical Data

Thickness* (adhesive and carrier)	11.5-mil		
Temperature resistance**	-4°F to +212°F		
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 2-mil polyester film)	cover side	open side	
	3.00 lb/in	1.60 lb/in	after 1 min
	3.43 lb/in	1.60 lb/in	after 20 min
	3.65 lb/in	1.83 lb/in	after 24 h
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 2-mil polyester film)	cover side	open side	
	2h	5h	at 73°F
	5 min	10 min	at 158°F
Shelf life**	2 years		
Application temperature	> +59°F		
Available lengths	27-yard, 55-yard		
Available widths (in inches)	39 Slit rolls: 1/2, 3/4, 1, 1 1/2, 2		

* average ** in original packaging, at 68°F and 50% relative humidity

IMPORTANT NOTICE

All ORABOND™ products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND™ products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND™ products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORABOND™ is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

techsupport-americas@orafol.com – www.orafol.com