



HP-2000 High Temperature Adhesive

HP-2000 High Temperature Adhesive is a high performance, synthetic rubber, web aerosol adhesive that is compliant in California. This product offers high initial tack for contact bonding, while also giving excellent bonds at elevated temperatures. HP-2000 forms strong permanent bonds between porous and non-porous surfaces such as insulation, metal, carpets, rubber, liners, foam, wood, plastic, and FRP. HP-2000 does not contain chlorinated solvents or ozone depleting substances and is light in color for no staining. HP-2000 has high water resistance and excellent temperature resistance. Typical applications for include bonding FRP to gel coat in marine applications, headliners, HPL, bonding difficult to bond plastics, bonding rubber to wood or metal, and bonding carpet to wood or metal.

Technology / Base	Synthetic Rubber
Type of Product	Aerosol Contact Adhesive
Components	One Component
Curing	Solvent Release
Appearance / Color	Light Amber/White
Consistency	Web Spray

Features and Benefits

- California Compliant
- Excellent Temperature Resistance
- Excellent Water Resistance
- High Tack and Excellent Adhesion Properties
- Excellent Bonding to Metals, Plastics, Wood, Laminates, Rubber, FRP, Gel Coat, Low Energy Plastics, Polyethylene, Polypropylene, SBR Rubber, Foam
- No Chlorinated Solvents
- No Ozone Depleting Substances
- Light Color with No Staining

Technical Data

Typical Properties	Value	Condition/Method
Solvents	Methyl Acetate, Cyclohexane, ZemaSol, Oxsol-100 (PCBTF), Propyl Acetate, Pentane and Hydrocarbon Propellant	
Solids Content by Weight	18%	
Density	6.32 lb/gal	
Spray Pattern	Web	
Dry Time	1-2 min	
Bonding Time	Up to 15 min	
Shelf Life	12 months in unopened container	when stored below 90°F
180° Peel Strength	15-20 lb/in	3 days at 73°F, ASTM D3330
Shear Adhesion Failure Temperature (SAFT)	240°F	ASTM D4498
Operating Temperature	-40°F to 130°F	



Surface Preparation

Clean, dry, dust-free surfaces are required for optimum bond strength. Surface temperatures should be maintained at temperatures above 40° F. The adhesive should be applied in smooth even coats to both surfaces and adequate pressure applied to assure complete contact.

Application Methods

- Shake can well before use.
- Always direct arrow & spray toward surface to be bonded, holding can 6-10 inches from bonding surface and apply in even coats.
- Always maintain product package in an upright position and hold parallel to substrate.
- Spray both surfaces and allow 1-4 minutes for drying.
- Bond both surfaces together with maximum uniform pressure over entire surface.
- Always test production pieces in typical bonding & operating conditions for best application techniques and compatibility.
- If clogging occurs, clean tip & valve with acetone.

Safety and Disposal

See SDS for safety information, warnings, precautions, personal protective equipment, and disposal information.

Clean-Up

Acetone is recommended for cleaning equipment and over spray. Other solvents will provide varying degrees of cleaning capability.

Precautionary Data

FLAMMABLE. Keep away from sparks and open flames.

- For Professional/Industrial use only.
- Keep away from children.
- Read label and Safety Data Sheet carefully before use.
- Do not puncture or incinerate containers.
- Do not store at temperatures above 120°F

Storage

Product should be stored in a cool dry place out of direct sunlight. The shelf life is from date of manufacture. Shelf life is based on the products being stored properly at temperatures between 55°F and 90°F.

www.hbfuller.com

Date Modified: 07 September 2022

Connecting what matters.™

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience, and we believe this information to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

© and ™ are trademarks of Royal Adhesives and Sealants, LLC and H.B. Fuller Company or one of its affiliated entities.

NOTE TO USER: by ordering/receiving product you accept the **Royal Adhesives and Sealants General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of Royal Adhesives and Sealants for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. Royal Adhesives and Sealants shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Royal Adhesives and Sealants, LLC
an H.B. Fuller Company
2001 W. Washington Street
South Bend, IN 46628
+1 800.999.GLUE



H.B. Fuller
www.hbfuller.com

©H.B. Fuller Company, 2022