



DIGITAL MEDIA APPLICATION INSTRUCTIONS

ColorPrint Easy For Use On: 100% Cotton | Poly/cotton blends | 100% Polyester | Leather



Print and Cut Instructions:

- Print, cut, and weed material
- No dry time required!
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 300°F / 149°C
- Use medium pressure for 15 seconds
- Peel carrier warm

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers

ColorPrint Extra PU For Use On: 100% Nylon | 100% Cotton | Poly/cotton blends | 100% Polyester | Leather



Print and Cut Instructions:

- Print, cut, and weed your design
- No dry time required!
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 305°F / 150°C
- Use medium pressure for 15 seconds
- Peel carrier hot or warm

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Wash inside-out for best results

Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers

ColorPrint PU (matte/gloss) For Use On: 100% Cotton | Poly/cotton blends | 100% Polyester | Leather | Lycra®/Spandex



Print and Cut Instructions:

- Set heater/dryer to 113°F/45°C
- If heavy saturation ink, dry 1 hour before cutting
- Print, cut, and weed material
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 295°F / 146°C
- Use medium pressure for 15-20 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers

DigiBrick™ For Use On: 100% Cotton | 100% polyester | Poly/cotton blends



Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 25 seconds
- Peel carrier cold

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on low dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers

EasyPSV® Printable For Use On: Glass | Wood | Plastic | Metal | Ceramic

Print and Cut Instructions:

- Print and cut your design (do not reverse/mirror)
- Weed excess vinyl

Application Instructions:

- Remove application tape's paper liner and place on top of EasyPSV
- Burnish with EasySqueegee® and lift tape with PSV away from liner
- Place on desired object and burnish with an EasySqueegee
- Peel away the application tape

Care:

- Not Microwave or Dishwasher Safe

Compatible with Eco-Solvent, Solvent, Latex and Mimaki UV Inks - Not compatible with Inkjet or Laser printers

Hi-5 Print Matte For Use On: 100% Cotton | Poly/cotton blends | 100% Polyester



Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 250°F / 120°C
- Use medium pressure for 5 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers

Recommended Accessories:

Siser® EasyWeeder®, EasySqueegee® parchment or multipurpose paper, or heat transfer cover sheet



*Due to variances in the manufacturing process of fabrics, Siser highly recommends testing prior to production

08-2023



DIGITAL MEDIA APPLICATION INSTRUCTIONS

SparklePrint™ For Use On: 100% Cotton | 100% polyester | Poly/cotton blends



Print and Cut Instructions:

- Print, cut, and weed material
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 311°F / 155°C
- Use medium/firm pressure for 15 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on low dryer setting
- Wash inside-out for best results

Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers

S-Print™ (Matte) For Use On: 100% Cotton | Poly/cotton blends | 100% Polyester | Spandex



Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Cover design with Heat Transfer Cover Sheet
- Apply design at 248°F / 120°C
- Use medium pressure for 10-15 seconds
- Peel carrier hot

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Dry on normal dryer setting

Compatible with Eco-Solvent and Solvent Inks - Not compatible with Inkjet or Laser printers

Sublithin® Soft For Use On: Sublimated | 100% Cotton | Poly/cotton blends | 100% Polyester



Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD Easy Mask or TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Apply design at 265°F / 130°C
- Use medium pressure for 15 seconds
- Peel carrier hot or warm

Laundering:

- Wait 24 hours before first wash
- Machine wash warm or cold with mild detergent
- Do not bleach or dry clean
- Wash inside-out for best results

Compatible with Eco-Solvent, Solvent and Latex Inks - Not compatible with Inkjet or Laser printers

ColorPrint Aurora™ For Use On: 100% Cotton | Poly/cotton blends | 100% Polyester



Print and Cut Instructions:

- Print, cut, and weed your design
- Mask with TTD High Tack Mask

Application Instructions:

- Preheat garment for 2-3 seconds
- Cover design with Heat Transfer Sheet
- Apply design at 305°F / 150°C
- Use medium pressure for 10-15 seconds
- Peel carrier hot or warm, 5-10 seconds off the press

Laundering:

- Wait 24 hours before first wash
- Machine wash cold with mild detergent
- Do not bleach or dry clean
- Dry on low dryer setting

Compatible with Eco-Solvent, Solvent and UV Inks - Not compatible with Inkjet or Laser printers

Recommended Accessories:

Siser® EasyWeeder®, EasySqueegee® parchment or multipurpose paper, or heat transfer cover sheet



SiserNA.com

*Due to variances in the manufacturing process of fabrics, Siser highly recommends testing prior to production

08-2023