



Holographic Series Printable

DATA SHEET

High glossy holographic film with excellent printability for a dazzling visual and stretchable for moderate curve.

Description

High performance glossy holographic silver printable and stretchable vinyl.

Face film	Calendered monomeric PVC
Thickness	100µm (4 mil) ±5%
Color and Finish	1000-H01X Holographic silver 1000-H02X Holographic shattered ice

Release liner

Premium quality paper imported from Japan.

Spec	90# double-PE coated silicone paper liner with air egress
Thickness	180 micron ±5%
Color and Finish	White with Graphictac branding

Adhesive

Clear acrylic, permanent non-residue, solvent-based adhesive, made in Taiwan

Thickness	32 micron ±2% clear acrylic
Apply Temp.	+10°C ~ +40°C
Adhesion (20 min)	1,000~1,100 g/25mm
Adhesion (24 hour)	1,200~1,300 g/25mm
Cohesion	24 hours ↑ with 1 kg loading

Application

Suitable for short-term visual effect on motorcycle / vehicle graphics, decoration and advertising graphics.

Printable with solvent, eco-solvent, UV and Latex system.

Durability

Shelf life: 1 year in original packaging, at 77°F (25°C) and 50% relative humidity.

Outdoor: With overlamine holographic properties will remain up to 18 months before fading, but PVC itself remains up to 3 years, depending on exposure angle and climate condition.

Length and Width

Length	100'
Width	20"/30"/54"

Temperature

Recommended application temperature: 59°F ~ 90°F (15°C~32°C, for optimum ease of use).

Service temperature: -22°F ~158°F (-30°C~+70°C, not for long periods of time at the extremes).