



## Polymeric Optically Clear Removable Printable

## DATA SHEET

Commercial grade media with removable adhesive for indoor use where clarity is crucial.

### Description

---

High performance ultra crystal clear polymeric film for inkjet printing.

Face film	Calendered polymeric PVC
Thickness	75µm (3mil) ±5%
Item# & Color	1000-P990R ultra crystal clear

### Release liner

---

High quality silicone coated PET made in Taiwan, offering extra clarity without orange peel effect, and traction coating to rid of statics during printing

Thickness	3mil (=75 micron) ±5%
Color and Finish	traction backed polyester liner with branding

### Adhesive

---

Clear acrylic, removable with high repositionability, solvent-based adhesive non-residue, made in Taiwan.

Thickness	25µm ±2%
Apply Temp.	+10°C ~ +40°C
Adhesion (20 min)	300 g/25mm
Adhesion (24 hour)	600 g/25mm
Cohesion	24 hours ↑ with 1 kg loading

### Application

---

Suitable for indoor graphics, decoration, advertising, wrapping on window / glass partition or applications that requires clarity.

Printable with solvent, eco solvent, UV and Latex printer.

### Storage

---

Shelf life is 1 years in original packaging, at 25°C and 50% relative humidity.

### Length and Width

---

Length	150'
Width	54"

### Temperature

---

Recommended application temperature: 15°C~32°C (for optimum ease of use).

Service temperature: -30°C~+70°C (not for long periods of time at the extremes).